

PRECISION BALANCES PARTNER WLC/C2




Balances series WLC C/2 are designed for fast and precise mass determination in laboratory and industrial conditions. They can also be used in areas with no access to mains (230V), as their standard equipment they include internal rechargeable battery and RS 232 output. All kinds of this balance (pan size: 128×128, and 195×195 mm) are equipped with stainless steel weighing platform and backlit LCD display providing good reading of weighing result.




Balances have possibility of weighing loads outside weighing platform (so called under hook weighing). where a load is hanged under the instrument. This is an alternative for weighing loads with non-standard dimensions and shapes.

- Counting pieces
- Checkweighing
- Animal weighing
- Percentage
- Caps lock of max indication
- Measurement in Newton

A1 version



A2 version



Technical data:

	WLC 0,6/A1/C2*	WLC 1/A2/C/2	WLC 1,2/A2/C/2	WLC 3/A2/C/2	WLC 6/A2/C/2 *
Max capacity	0,6 kg	1 kg	1,2 kg	3/6 kg	6 kg
Readability	0,01 g	0,01 g	0,02 g	0,05 g	0,1 g
Tare range	-0,6 kg	-1 kg	-3 kg	-6 kg	-6 kg
Repeatability	0,02 g	0,03 g	0,02 g	0,05 g	0,2 g
Linearity	±0,2 g	±0,03 g	±0,02 g	±0,05 g	±0,2 g
Pan size	128 × 128 mm	195 × 195 mm			
Power supply	230V / 11V AC or 120V / 11V AC, and accumulator				
Calibration	internal (automatic)				
IP rating	IP 43				
Stabilization time	3 s				
Working temperature	+15° - +30 °C				
Display	LCD (backlit)				

* verified balances

Additional equipment:

"KAFKA" THERMAL PRINTER	EXTERNAL RECHARGEABLE BATTERY PACK
NEEDLE PRINTER "EPSON"	SUITCASE FOR BALANCE
RACK FOR UNDER HOOK WEIGHING	COMPUTER SOFTWARE: PW-WIN 2005, RAD-KEY 2000
LCD ADDITIONAL DISPLAY	

PARTNER CORPORATION

Str. Mures nr.63,Bucuresti ,Sector 1 * Tel/fax : 021-2242257 * e-mail:office@partner.com.ro * www.partner.com.ro